

PRODUCT DETAILS

Material:

316 SS and 304 SS

Standards:


ASTM A312

Country of Origin:

100% Made in USA

APPLICATION

- · Bent sections of rigid conduit that help in changing the direction of conduit
- Standard radius, 45°
- Threaded on both ends, NPT
- Offered in Type 316 SS and Type 304 SS
- · Supplied with two thread protectors
- · Manufactured in stainless steel to help prevent corrosion
- Can be installed using ordinary hand tools and require little maintenance or repair
- · Provided in a bright, polished finish that does not require touch up or painting



Part		Weight/ Each (lbs.)				
Number	Size		A	В	Ć	D
ELB50-45	½ in.	1	7.08	2.93	4.00	2.49
ELB75-45	¾ in.	1	7.42	3.07	4.50	2.48
ELB100-45	1 in.	1	8.96	3.71	5.75	2.87
ELB125-45	1-¼ in.	2	10.40	4.31	7.25	3.09
ELB150-45	1-½ in.	3	12.04	4.99	8.25	3.64
ELB200-45	2 in.	5	14.54	6.02	9.50	4.58
ELB250-45	2-½ in.	9	16.39	6.79	10.50	5.25
ELB300-45	3 in.	13	19.15	7.93	13.00	5.83
ELB400-45	4 in.	22	21.50	8.91	16.00	5.97

Note: Type 316 SS part numbers listed above. Type 304 SS products are denoted by adding "-304SS." For example ELB75-45-304SS.

