
STAINLESS STEEL **FDX DEVICE BOXES**



APPLICATION

- Used to wire devices such as switches and receptacles, act as pull boxes, and/or connect conduit
- Offered in "deep" style, in six configurations: FD, FDC, FDA, FDS, FDX, and double-gang FDDX
- · Manufactured in stainless steel to help prevent corrosion
- · Can be installed using ordinary hand tools and require little maintenance or repair
- Provided in a bright, polished finish that does not require touch up or painting



PRODUCT DETAILS


Material: -Body: CF8M (316 SS) -Grounding Screw: 316 SS

Standards: ASTM A351, ASTM F593

Country of Origin: 100% Made in USA

UL File Number: QCIT.E300676 (Standard 514A)

Canada UL File Number: DWTT7.E300676 (Standard 514A)



Part	Conduit	Weight/	Dimension (in.)					
Number	Size	Each (lbs.)	Α	В	C	D	E	F
FDX75	3⁄4 in.	4	6.19	4.63	2.94	2.94	1.31	4.50



PO BOX 847, GREENSBURG, PA 15601 PHONE: 1-800-945-4316 • FAX: 724-838-1544 WEB: GIBSONSTAINLESS.COM

© 2015 GIBSON STAINLESS & SPECIALTY, INC. - REV 12/2015