
STAINLESS STEEL LB CONDUIT BODIES





PRODUCT DETAILS

Material:

-Body: CF8M (316 SS) -Cover, Screws: 316 SS -Gasket: Neoprene

Country of Origin: 100%

Made in USA


UL File Number: QCIT.E300676 (Standard 514A)

(Standard 514A)

Canada UL File Number: DWTT7.E300676

APPLICATION

- Designed to make 90° turns, change the route of conduit, and/or to make wiring pulls and connections
- Flat back design provides extra wiring capacity
- Form 8
- Offered in seven configurations: C, LB, LL, LR, T, TB, X
- · Supplied complete with cover, gasket and Type 316 SS screws
- · Manufactured in stainless steel to help prevent corrosion
- Can be installed using ordinary hand tools and require little maintenance or repair
- · Provided in a bright, polished finish that does not require touch up or painting



Part		Weight/	Dimension (in.)				
Number	Size	Each (lbs.)	Α	В	C`	Ď	E
7050LB	½ in.	1	4.86	3.50	2.05	1.34	1.18
7075LB	¾ in.	2	5.80	4.31	2.50	1.63	1.50
7100LB	1 in.	3	6.63	5.00	2.83	2.00	1.75
7125LB	1-¼ in.	5	7.75	6.00	3.50	2.49	2.15
7150LB	1-½ in.	5	8.43	6.58	3.72	2.73	2.33
7200LB	2 in.	9	10.55	8.50	4.38	3.38	2.75
7300LB	3 in.	18	13.58	11.25	6.13	4.63	4.04
7400LB	4 in.	28	16.60	13.75	7.20	5.56	5.13

